

S Series  
Dual Seal  
Waterproof Toggle



IP68 Rated

# General Specifications

## Electrical Capacity (Resistive Load)

**Power Level:** Shown in following tables

## Other Ratings

- Contact Resistance:** 10 milliohms maximum
- Insulation Resistance:** 1,000 megohms minimum @ 500V DC
- Dielectric Strength:** 2,000V AC minimum for 1 minute minimum
- Mechanical Life:** 50,000 operations minimum for S1AWB, S2AWB, S3AWB, S6AWB, S7AWB, S21AWB  
30,000 operations minimum for S5AWB, S8AWB, S25AWB, S28AWB
- Electrical Life:** 25,000 operations minimum
- Angle of Throw:** Shown in following tables

## Environmental Data

**Operating Temperature Range:** -30°C through +70°C (-22°F through +158°F)

**Sealing:** Waterproofing, achieved with boot at base of lever plus o-rings inside and outside of bushing, meets IP68 of IEC60529 Standards (dust tight and protection against effects of temporary immersion). See further explanation on last page.

## Processing

**Soldering:** Manual Soldering: 390°C for 4 seconds, 2 cycles

# Distinctive Characteristics


Dual protection with internal o-ring and external rubber washer, sealing the switch to achieve IP68 of IEC 60529 Standards (dust tight and water protected against immersion for as long as 30 minutes, in 1.5 meters of water).

Additional panel seal security against wet environments provided by waterproof boot at base of toggle.


Fluid actuation delivered in smooth, sturdy tactile feel.

Sleek design incorporates functionality with polished, chrome-plated actuator paired with waterproof boot.

Superb quality and construction design prohibit entry of foreign particles that may otherwise compromise lever operation.



## SINGLE POLE WITH SOLDER LUG


Model	Pole & Throw	Toggle Position/Connected Terminals NONE = No Position ( ) = Momentary			Electrical Capacity			$\alpha$ = Angle of Throw		
		Up	Center	Down	Resistive					
					AC 125V	AC 250V	DC 30V			
S1AWB	SPST	ON	1-3	NONE	OFF	—	15A	6A	20A	$24^\circ \pm 4^\circ$
S2AWB	SPDT	ON	2-3	NONE	ON	2-1	15A	6A	20A	$24^\circ \pm 4^\circ$
S3AWB	SPDT	ON	2-3	OFF	ON	2-1	15A	6A	20A	$24^\circ \pm 4^\circ$
S5AWB	SPDT	ON	2-3	NONE	(ON)	2-1	15A	6A	20A	$20^\circ \pm 4^\circ$
S8AWB	SPDT	(ON)	2-3	OFF	(ON)	2-1	15A	6A	20A	$24^\circ$

Throw &amp; Schematics:

SPST






SPDT




Note: Terminal numbers are actually on the switch

## DOUBLE POLE WITH SOLDER LUG


Model	Pole & Throw	Toggle Position/Connected Terminals NONE = No Position ( ) = Momentary			Electrical Capacity			$\alpha$ = Angle of Throw			
		Up	Center	Down	Resistive						
					AC 125V	AC 250V	DC 30V				
S21AWB	DPST	ON	1-3 4-6	NONE	OFF	—	—	15A	15A	15A	$24^\circ \pm 4^\circ$
S6AWB	DPDT	ON	2-3 5-6	NONE	ON	2-1 5-4	15A	10A	20A	$24^\circ \pm 4^\circ$	
S7AWB	DPDT	ON	2-3 5-6	OFF	ON	2-1 5-4	15A	10A	20A	$24^\circ \pm 4^\circ$	
S25AWB	DPDT	ON	2-3 5-6	NONE	(ON)	2-1 5-4	15A	6A	20A	$20^\circ \pm 4^\circ$	
S28AWB	DPDT	(ON)	2-3 5-6	OFF	(ON)	2-1 5-4	15A	6A	20A	$24^\circ \pm 4^\circ$	

Throw &amp; Schematics:

DPST








DPDT




Note: Terminal numbers are actually on the switch


## STANDARD HARDWARE

AT503M Hex Face Nut  
Brass with Chrome PlatingLockwasher  
Phosphor Bronze/ChromateAT537 O-ring  
Nitrile Butadiene Rubber

## PANEL CUTOUT



Anti-rotation



No Anti-rotation

Maximum Effective Panel Thickness  
.157" (4.0mm)


## TYPICAL SWITCH DIMENSIONS

### Solder Lug




**S2AWB**

### Single Pole



S1AWB does not have terminal 2




### Solder Lug




**S6AWB**

### Double Pole



S21AWB does not have terminals 2 & 5



## APPLICATION CONSIDERATIONS

The Dual Seal Waterproof S Toggle is designed as a panel seal switch, and not to be used under water.

### Material Properties


The material for the waterproof boot is silicone rubber. While silicone rubber has excellent heat, cold and weather resistant properties, it has less durability and oil resistance.

The o-ring below the panel is made of nitrile butadiene rubber, which excels in durability and oil and chemical resistance. Its performance is less durable with lower weather and ozone resistant characteristics.

Evaluate the products in regard to your application and intended environment with these properties in mind.

### Waterproof Test Conditions


Waterproofing is measured by submerging the switch 5 centimeters from the water surface (see illustration), and opening and closing 50 times at a frequency of 50 – 60 times per minute. The switch is then submersed 1.5 meters from the surface and left in this position for 30 minutes. Repeat opening and closing



same as previous test. The resulting insulation resistance and voltage capacity are both within the rated values, and water has not entered inside the switch or installation panel.

### Panel Installation

For panel installation, the internal tooth lockwasher is installed above the panel. The external o-ring mounts below the panel.



### Applications

- Construction Equipment
- Hospitality and Restaurant
- Transportation
- Medical Equipment
- Machine Tooling
- Marine Equipment \*

\* Salt spray tested as per Mil-STD-810G section 509.5.

**Effective Date** October 2018

**NKK**  
SWITCHES

7850 East Gelding Drive • Scottsdale, AZ 85260 • Telephone 480.991.0942 • Fax 480.998.1435

[www.nkkswitches.com](http://www.nkkswitches.com) • 1.877.2BUYNKK (228.9655)