

PRINTED

11-30-79E				
LL771-1				
CHANGE SHT. NO.				

CAUTION

P.C. BOARD CAN BE DAMAGED BY STATIC ELECTRICITY

Before removing P.C. board from static shielding bag or equipment, remove your body static charge by touching unpainted grounded frame of equipment. Remove P.C. board from shielding bag and place directly into equipment. Shorting jumpers (if used) are not to be removed until installation is complete.

P.C. boards being returned to The Lincoln Electric Company for credit must be placed in the static shielding bag. Failure to follow this procedure can damage the P.C. board and prevent proper failure analysis.



ECM Electronic

Autoryzowany serwis spawarek oraz zgrzewarek krajowych i zagranicznych. Automatyka przemysłowa.



Nasze strony: www.spaw-serwisch.pl * ecm-electronic.pl

Dystrybucja, serwis, sprzedaż - kontakt:

e-mail: spawserwisch@gmail.com, biuro@ecm-electronic.pl

tel. kont.: +48 501 283 621, +48 34 368 1578 (z fax.)



UNLESS OTHERWISE SPECIFIED TOLERANCE:
ON HOLE SIZES PER E-2056
ON MATERIAL ("Y") TO AGREE WITH PUBLISHED STANDARDS.

ON 2 PLACE DECIMALS IS $\pm .02$
ON 3 PLACE DECIMALS IS $\pm .002$
ON ALL ANGLES IS $\pm .5$ OF A DEGREE

THE LINCOLN ELECTRIC CO.
CLEVELAND, OHIO U. S. A.

EQUIP.
TYPE

Misc. P.C. Boards

SUBJECT

Handling Instructions

SCALE

~

DR

DATE 10-1-79

CHK

SUP'S'D'G

SHT. NO. T-14477